

规格书

WIRE SPECIFICATION

规格型号 SPEC NO.	Soft Silicone wire 10AWG	参照标准 REFERENCE STANDARD	UL758
额定温度 RATED TEMPERATURE	200℃	额定电压 RATED VOLTAGE	600V-DC
阻燃等级 FLAME RETARDANT GRADE	VW-1	环保标准 ENVIRONMENTAL STANDARDS	RoHS

结构项目 CONSTRUCTION ITEM			
导体 CONDUCTOR	构造规格 SECTIONAL AREA	AWG/ mm	1050/0.08TS±0.003TS
	导体材质 MATERIAL	Tinned Copper
	截面积 SECTIONAL AREA	mm ²	5.3
	绞合外径 STRANDED DIAMETER	mm	2.99
绝缘 INSULATION	材质 MATERIAL	Silicone
	平均厚度 THE AVERAGE THICKNESS	mm	1.3
	最小厚度 MINIMUM GAUGE	mm	1.2
	颜色 COLOR	Black/RED
	绝缘外径 INSULATION DIAMETER	mm	5.4±0.10
屏蔽隔离 SHIELDING	包带 COVERING	/
	屏蔽方式 SCREEN MODE	/
	构造规格 SECTIONAL AREA	AWG/ mm	/
	屏蔽材质 MATERIAL	/
	绞合总外径 TOTAL DIAMETER	mm	/
外被 JACKET	材质 MATERIAL	/
	平均厚度 THE AVERAGE THICKNESS	mm	/
	最小厚度 MINIMUM GAUGE	mm	/
	颜色 COLOR	/
	线材外径 OVERALL DIAMETER	mm	/

印字内容 PRINTING CONTENT	10AWG 200℃
-----------------------	------------

